

KLBUE 3-8 FM4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Thanks to special mounting feet, the product portfolio also includes shield clamping saddles that can be mounted on the TS 35 DIN rail. The shield is diverted from the shield clamping saddles via the mounting foot to the TS 35 mounting rail and thus to PE (ground).

General ordering data

Version	Clamping yoke, Clamping yoke for shield connection
Order No.	1252530000
Type	KLBUE 3-8 FM4
GTIN (EAN)	4032248112531
Qty.	10 pc(s).

KLBUE 3-8 FM4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	26 mm	Depth (inches)	1.024 inch
Height	50 mm	Height (inches)	1.969 inch
Width	14.5 mm	Width (inches)	0.571 inch
Net weight	15.136 g		

Temperatures

Storage temperature	-25 °C...55 °C	Ambient temperature	-5 °C...40 °C
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C

Material data

Colour	silver	UL 94 flammability rating	None
--------	--------	---------------------------	------

System specifications

End cover plate required	No	Rail	TS 35
--------------------------	----	------	-------

Additional technical data

Explosion-tested version	No	Installation advice	TS 35
Type of mounting	Snap-on		

Conductors for clamping (rated connection)

Cable diameter, max.	8 mm	Cable diameter, min.	3 mm
Connection cross-section, stranded, max.	8 mm ²	Connection cross-section, stranded, min.	3 mm ²
Stripping length	18 mm	Type of connection	Spring connection

General

Installation advice	TS 35	Rail	TS 35
---------------------	-------	------	-------

Rating data

Rated cross-section	8 mm ²
---------------------	-------------------

Classifications

ETIM 6.0	EC002020	ETIM 7.0	EC002020
ETIM 8.0	EC002020	ETIM 9.0	EC002020
ETIM 10.0	EC002020	ECLASS 9.0	27-14-11-50
ECLASS 9.1	27-14-11-50	ECLASS 10.0	27-14-11-50
ECLASS 11.0	27-14-11-50	ECLASS 12.0	27-14-11-50
ECLASS 13.0	27-25-01-20	ECLASS 14.0	27-25-01-20
ECLASS 15.0	27-25-01-20		

Environmental Product Compliance

RoHS Compliance Status	Compliant without exemption
REACH SVHC	No SVHC above 0.1 wt%

KLBUE 3-8 FM4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Approvals

ROHS	Conform
------	---------

Downloads

Engineering Data	CAD data – STEP
User Documentation	Beipackzettel_KLBUE.pdf StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format
Brochures	