

**DKB CC DIA 30****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**General ordering data**

|            |                                          |
|------------|------------------------------------------|
| Version    | MetalliCard, Adhesive strip, Transparent |
| Order No.  | <a href="#">1341180000</a>               |
| Type       | DKB CC DIA 30                            |
| GTIN (EAN) | 4050118145618                            |
| Qty.       | 200 pc(s).                               |

## DKB CC DIA 30

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|          |         |                |         |
|----------|---------|----------------|---------|
| Depth    | 0.01 mm | Depth (inches) | 0 inch  |
| Diameter | 30 mm   | Net weight     | 0.275 g |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -40...160 °C |
|-----------------------------|--------------|

## General data

|                                      |                                |             |
|--------------------------------------|--------------------------------|-------------|
| Adhesive                             | Modified acrylate              |             |
| Colour                               | Transparent                    |             |
| Material                             | Polyester film                 |             |
| Number of markers per combination    | 1 MetalliCard = Adhesive strip |             |
| Number of markers per packaging unit | Form of supply                 | MetalliCard |
| Operating temperature range          | -40...160 °C                   |             |
| Operating temperature range, max.    | 160 °C                         |             |
| Operating temperature range, min.    | -40 °C                         |             |
| Recommended industries               | Energy, Process                |             |
| Version                              | Self-adhesive                  |             |

## Device markers

|          |       |
|----------|-------|
| Diameter | 30 mm |
|----------|-------|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001288    | ETIM 7.0    | EC001288    |
| ETIM 8.0    | EC001288    | ETIM 9.0    | EC001288    |
| ETIM 10.0   | EC001288    | ECLASS 9.0  | 27-40-06-29 |
| ECLASS 9.1  | 27-40-06-29 | ECLASS 10.0 | 27-40-06-29 |
| ECLASS 11.0 | 27-28-11-04 | ECLASS 12.0 | 27-28-11-04 |
| ECLASS 13.0 | 27-28-11-04 | ECLASS 14.0 | 27-28-11-04 |
| ECLASS 15.0 | 27-28-11-04 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|            |                                          |
|------------|------------------------------------------|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|------------------------------------------|

### DKB CC DIA 30

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Example of use

