

**ModuPlug
HDC MDU****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Flexible**

The four module sizes make for individual plug solutions that save a huge amount of space. The smaller pitch translates into an optimised design too.

General ordering data

Type	HDC MDU
Order No.	1429040000
Version	Dummy module
GTIN (EAN)	4050118233421
Qty.	1 pc(s).

**ModuPlug
HDC MDU**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	7.15 mm	Width (inches)	0.281 inch
Height	20.6 mm	Height (inches)	0.811 inch
Depth	34 mm	Depth (inches)	1.339 inch
Net weight	2.58 g		

Temperatures

Limit temperature	-40 °C ... 125 °C
-------------------	-------------------

General data

Insulation strength	$10^{12} \Omega$	Material	Polycarbonate, glass fibre reinforced
Plugging cycles	≥ 500	Pollution severity	3
Required plug-in slots	0.5	Series	ModuPlug
UL 94 flammability rating	V-0		

Design

Product family	ModuPlug	Product type	Dummy module
----------------	----------	--------------	--------------

General descriptions

Plugging cycles	≥ 500
-----------------	------------

Material

UL 94 flammability rating	V-0	Material	Polycarbonate, glass fibre reinforced
---------------------------	-----	----------	---------------------------------------

Classifications

ETIM 6.0	EC002312	ETIM 7.0	EC002312
eClass 9.0	27-44-02-92	eClass 9.1	27-44-02-18
eClass 10.0	27-44-02-92		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN FL FIELDWIRING EN
Engineering Data	EPLAN
Engineering Data	STEP

ModuPlug HDC MDU

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

