

**H0,34/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

For conductors from 0.25 to 6,0 mm<sup>2</sup> (AWG 24 - 10)

tin-plated copper

dimensional tolerances to DIN 46228 part 1

- supplied loose in polybag

**General ordering data**

|            |                                            |
|------------|--------------------------------------------|
| Version    | Wire-end ferrule, Standard, 5 mm, 5 mm, No |
| Order No.  | <a href="#">1475640000</a>                 |
| Type       | H0,34/5                                    |
| GTIN (EAN) | 4050118282238                              |
| Qty.       | 1,000 pc(s).                               |
| Packaging  | loose                                      |

**H0,34/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

|            |         |
|------------|---------|
| Net weight | 0.023 g |
|------------|---------|

**Technical data**

| Description of article | Wire end ferrule without plastic collar | Version | Standard |
|------------------------|-----------------------------------------|---------|----------|
|------------------------|-----------------------------------------|---------|----------|

**Wire-end ferrules**

|                                         |         |                             |                      |
|-----------------------------------------|---------|-----------------------------|----------------------|
| Collar diameter (D2)                    | 1.8 mm  | Conductor cross-section     | 0.34 mm <sup>2</sup> |
| Contact surface diameter (D1)           | 0.85 mm | Contact surface length (L2) | 5 mm                 |
| L1 in mm                                | 5 mm    | Stripping length            | 5 mm                 |
| Wire connection cross section AWG, max. | AWG 22  |                             |                      |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ETIM 10.0   | EC000005    | ECLASS 9.0  | 27-40-02-01 |
| ECLASS 9.1  | 27-40-02-01 | ECLASS 10.0 | 27-40-02-01 |
| ECLASS 11.0 | 27-40-02-01 | ECLASS 12.0 | 27-40-02-01 |
| ECLASS 13.0 | 27-40-02-01 | ECLASS 14.0 | 27-40-02-01 |
| ECLASS 15.0 | 27-40-02-01 |             |             |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

**Approvals**

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate no. (cULus) | E499744    |

**Downloads**

|                                             |                                           |
|---------------------------------------------|-------------------------------------------|
| Approval/Certificate/Document of Conformity | <a href="#">Certificate of Compliance</a> |
| Catalogues                                  | <a href="#">Catalogues in PDF-format</a>  |

**H0,34/5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

