

**AP DLD2.5/PE DB****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Product image**

To ensure the finger safety and the compliance to the required clearance and creepage distances, an end plate has to be placed at the end of a plug.

**General ordering data**

|            |                                                                                                |
|------------|------------------------------------------------------------------------------------------------|
| Version    | End plate for terminals, dark beige, Height: 47.51 mm, Width: 1.5 mm, V-O, Wemid, Snap-on: Yes |
| Order No.  | <a href="#">1783800000</a>                                                                     |
| Type       | AP DLD2.5/PE DB                                                                                |
| GTIN (EAN) | 4032248189830                                                                                  |
| Qty.       | 20 pc(s).                                                                                      |

## AP DLD2.5/PE DB

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Depth      | 45.85 mm | Depth (inches)  | 1.805 inch |
| Height     | 47.51 mm | Height (inches) | 1.87 inch  |
| Width      | 1.5 mm   | Width (inches)  | 0.059 inch |
| Net weight | 3.685 g  |                 |            |

## Temperatures

|                                  |                |                                  |               |
|----------------------------------|----------------|----------------------------------|---------------|
| Storage temperature              | -25 °C...55 °C | Ambient temperature              | -5 °C...40 °C |
| Continuous operating temp., min. | -50 °C         | Continuous operating temp., max. | 120 °C        |

## Material data

|                           |       |        |            |
|---------------------------|-------|--------|------------|
| Material                  | Wemid | Colour | dark beige |
| UL 94 flammability rating | V-0   |        |            |

## System specifications

|         |           |
|---------|-----------|
| Version | End plate |
|---------|-----------|

## Additional technical data

|         |     |
|---------|-----|
| Snap-on | Yes |
|---------|-----|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000886    | ETIM 7.0    | EC000886    |
| ETIM 8.0    | EC000886    | ETIM 9.0    | EC000886    |
| ETIM 10.0   | EC000886    | ECLASS 9.1  | 27-14-11-33 |
| ECLASS 10.0 | 27-14-11-33 | ECLASS 11.0 | 27-14-11-33 |
| ECLASS 12.0 | 27-14-11-33 | ECLASS 13.0 | 27-25-03-01 |
| ECLASS 14.0 | 27-25-03-01 | ECLASS 15.0 | 27-25-03-01 |

Cradle to gate 0.039 kg CO2eq.

## Environmental Product Compliance

|                          |                                              |
|--------------------------|----------------------------------------------|
| RoHS Compliance Status   | Compliant without exemption                  |
| REACH SVHC               | No SVHC above 0.1 wt%                        |
| Product Carbon Footprint | de.myview.objectmodel.impl.BlockImpl@48ffebe |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Engineering Data   | <a href="#">CAD data – STEP</a>                 |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>        |