

**SM 36/18-30 MM WS VPE100****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)**Prevention of incorrect operation: SM**

MultiMark device markers can be used with marking materials from different manufacturers. Wherever they are used, they ensure that all components, such as control and signalling devices from different vendors, are clearly assigned.

**Your benefits with MultiMark**

- "Different materials for various requirements"
- Can be used with equipment from many manufacturers
- Device markers with a familiar design

**General ordering data**

|                    |                                                       |
|--------------------|-------------------------------------------------------|
| Version            | SwitchMark, Device markers, 56 x 36 mm, white         |
| Order No.          | <a href="#">2497020000</a>                            |
| Type               | SM 36/18-30 MM WS VPE100                              |
| GTIN (EAN)         | 4050118508529                                         |
| Qty.               | 100 pc(s).                                            |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> |

## SM 36/18-30 MM WS VPE100

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|          |        |                 |            |
|----------|--------|-----------------|------------|
| Depth    | 0.1 mm | Depth (inches)  | 0.004 inch |
| Height   | 56 mm  | Height (inches) | 2.205 inch |
| Width    | 36 mm  | Width (inches)  | 1.417 inch |
| Diameter | 30 mm  | Net weight      | 0.056 g    |

## Temperatures

|                             |              |
|-----------------------------|--------------|
| Operating temperature range | -40...120 °C |
|-----------------------------|--------------|

## General data

|                                   |                   |                                   |                             |
|-----------------------------------|-------------------|-----------------------------------|-----------------------------|
| Adhesive                          | Acrylate adhesive | Approval acc. to UL 969           | Yes                         |
| Colour                            | white             | Halogen                           | No                          |
| Material                          | Polyester         | Operating temperature range       | -40...120 °C                |
| Operating temperature range, max. | 120 °C            | Operating temperature range, min. | -40 °C                      |
| Printed characters                | without           | Size of labelling field           | 18 x 36 mm                  |
| UL 94 flammability rating         | V-0               | Version                           | halogen-free, Self-adhesive |
| Width                             | 36 mm             |                                   |                             |

## Device markers

|          |       |         |    |
|----------|-------|---------|----|
| Diameter | 30 mm | Halogen | No |
|----------|-------|---------|----|

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001288    | ETIM 7.0    | EC001288    |
| ETIM 8.0    | EC001288    | ETIM 9.0    | EC001288    |
| ETIM 10.0   | EC001288    | ECLASS 9.0  | 27-40-06-29 |
| ECLASS 9.1  | 27-40-06-29 | ECLASS 10.0 | 27-40-06-29 |
| ECLASS 11.0 | 27-28-11-04 | ECLASS 12.0 | 27-28-11-04 |
| ECLASS 13.0 | 27-28-11-04 | ECLASS 14.0 | 27-28-11-04 |
| ECLASS 15.0 | 27-28-11-04 |             |             |

## Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

## Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

## Downloads

|            |                                          |
|------------|------------------------------------------|
| Catalogues | <a href="#">Catalogues in PDF-format</a> |
|------------|------------------------------------------|

**SM 36/18-30 MM WS VPE100**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

