

CRIMPFIX ECO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

- For automatic stripping and crimping
- Time-saving and efficient processing
- Easily adjustable to the respective cross-section range
- Stripping and crimping in one work step
- The processing of sleeves or contacts from other manufacturers can cause machine failures and defects!

General ordering data

Version	Automatic machines, Automatic stripper and crimper
Order No.	2833890000
Type	CRIMPFIX ECO
GTIN (EAN)	4064675422570
Qty.	1 pc(s).
Replacement parts	2875560000 2875570000

CRIMPFIX ECO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	323 mm	Depth (inches)	12.717 inch
Height	188 mm	Height (inches)	7.402 inch
Width	230 mm	Width (inches)	9.055 inch
Net weight	12,496 g		

PW65 maintenance - automatic stripping/crimping

Consumables	Linked wire-end ferrules	Crimping	Trapezoidal
Crimping length	8 mm	Crimping range, max.	2.5 mm ²
Crimping range, min.	0.5 mm ²	Drive	Electro-mechanical
Electrical connection	100-240 V / 50/60 Hz / 100 VA	Length of wire-end ferrule	14 mm
Pulse time	approx. 1.5 s	Stripping range	0.5 - 2.5 mm ² (~ AWG 20-14)
Wire end ferrules cross-section, max.	2.5 mm ²	Wire end ferrules cross-section, min.	0.5 mm ²

Classifications

ETIM 6.0	EC002778	ETIM 7.0	EC002778
ETIM 8.0	EC002778	ETIM 9.0	EC002778
ETIM 10.0	EC002778	ECLASS 9.0	17-13-01-01
ECLASS 9.1	17-13-01-01	ECLASS 10.0	17-13-01-01
ECLASS 11.0	17-13-01-01	ECLASS 12.0	17-13-01-01
ECLASS 13.0	17-13-01-01	ECLASS 14.0	17-13-01-01
ECLASS 15.0	17-13-01-01		

Environmental Product Compliance

RoHS Compliance Status	Compliant with exemption
RoHS Exemption (if applicable/known)	6c, 7a, 7cl
REACH SVHC	Lead 7439-92-1
SCIP	d2df479e-2b79-4e98-adc7-b03577df98ae

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	OPIN CRIMPFIX ECO WEB
Catalogues	Catalogues in PDF-format