

**Industrial Ethernet
IE-C5ED8UG-MW****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Bulk stock, copper cable, flexible, 4 x 2 x AWG 26/7, Cat.
5, PUR, drag-chain compatible

General ordering data

Type	IE-C5ED8UG-MW
Order No.	8936390000
Version	Dragline cable, Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B), PUR, Products sold by meter, from 110 m
GTIN (EAN)	4032248713646
Qty.	1 m

Industrial Ethernet IE-C5ED8UG-MW

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Net weight	54.2 g	Insulation cross-section	0.95 mm
------------	--------	--------------------------	---------

Temperatures

Operating temperature, max.	80 °C	Operating temperature, min.	-40 °C
Storage temperature, max.	80 °C	Storage temperature, min.	-40 °C
Operating temperature	-40 °C...80 °C	Storage temperature	-40 °C...80 °C
Installation temperature	-20 °C...60 °C		

Electrical properties

Insulation strength	500,000 Ω
---------------------	-----------

Standards

Impervious to smoke	According to IEC 61034-2	Standard, assembly	UL-Style 20963 (80°C/30V)
Standard, insulating material	DIN EN 50290-2-25 (HD 624.5)	Standard, wire material	DIN EN 13602 Cu-ETP-A
Standard, shielding material	DIN EN 13602 Cu-ETP-A..B		

Cable structure

Wire material	Stranded tin-plated copper wire	Standard designations	LI9Y(ST)C11Y 4X2X0.14 VZN GN, SF/UTP
Strands	7	Cross-section	4*2*AWG 26/7 - 4*2*0.128 mm ²
Insulation cross-section	0.95 mm	Wire core insulation thickness	0.23 mm
Arrangement of wire cores	Twisted pair	Diameter of wire pair	1.9 mm
Colour sequence or wires - wire pairs	white/blue - blue, white/ orange - orange, white/ green - green, white/ brown - brown	Filler	As central element, Between the individual wire pairs
Shielding	SF/UTP	Complete shielding	Plastic foil, Aluminium foil, Shielding braid made from copper wiring
Shielding braid thickness	0.1 mm	Overlap of shielding braid	90 %
Material sheath	PUR	Sheath diameter, min.	6.3 mm
Sheath diameter, max.	6.8 mm	Sheathing material thickness	0.85 mm
Sheathing colour	green (RAL 6018)		

Electrical properties of cable

Category	Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)	Operating voltage (UL rating)	30 V undefined
Test voltage: wire-wire-shield	700 V _{rms} , 50 Hz, 1 min	Characteristic impedance	100 ± 5 Ω at 100MHz
Loop resistance	270 Ω/km	Deviation	40 ns/100m
Resistance differential	2 %	Transfer impedance	100 mΩ/m at 10 MHz
Insulation strength	500,000 Ω	Capacity at 800 Hz	50 nF/km
Signal propagation time	5.55 ns/m	Speed	180 m/min

Industrial Ethernet IE-C5ED8UG-MW

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Mechanical and material properties of cable

Min. bending radius, once only	4 x cable diameter	Min. bending radius, repetitive	7.5 x cable diameter
Bending cycles	5 Mio	Pulling force	≤ 100 N
Speed	180 m/min	Acceleration	5 m/s ²
Torsion resistance	30 °/m	Abrasion resistance	very good
Resistance to spread of flame	in accordance with IEC 60332-1	Resistance to oils	in accordance with IEC 60811-2-1
UV-resistant	Yes	Silicone-free	Yes
Halogen	halogen-free, according to IEC 60754-2	Impervious to smoke	According to IEC 61034-2
Fire propagation	No		

Classifications

ETIM 6.0	EC000830	ETIM 7.0	EC003249
eClass 9.0	27-06-18-05	eClass 9.1	27-06-90-90
eClass 10.0	27-06-18-01	UNSPSC	30-21-18-01

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 9 IETH 18/19 EN FL FIELDWIRING EN PI PROFINET CABLING EN
Engineering Data	WSCAD
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN

Industrial Ethernet IE-C5ED8UG-MW

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Detailed drawing

