

**Connecting elements**  
**H25,0/25****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



For conductors from 10.0 to 185.0 mm<sup>2</sup> (AWG 7 - 350 MCM)

tin-plated copper

dimensional tolerances to DIN 46228 part 1

- supplied loose in poly-bag

**General ordering data**

|            |                                      |
|------------|--------------------------------------|
| Type       | H25,0/25                             |
| Order No.  | <a href="#">9004170000</a>           |
| Version    | Wire-end ferrule, uninsulated, 25 mm |
| GTIN (EAN) | 4008190021863                        |
| Qty.       | 250 pc(s).                           |
| Packaging  | loose                                |

## Connecting elements

### H25,0/25

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |       |                |            |
|------------|-------|----------------|------------|
| Width      | 25 mm | Width (inches) | 0.984 inch |
| Net weight | 1.1 g |                |            |

### Technical data

|         |             |
|---------|-------------|
| Version | uninsulated |
|---------|-------------|

### Wire-end ferrules

|                               |        |                                         |                    |
|-------------------------------|--------|-----------------------------------------|--------------------|
| Collar diameter (D2)          | 9.5 mm | Conductor cross-section                 | 25 mm <sup>2</sup> |
| Contact surface diameter (D1) | 7.3 mm | L1 in mm                                | 25 mm              |
| Stripping length              | 25 mm  | Wire connection cross section AWG, max. | AWG 3              |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0   | EC000005    |
| eClass 9.0  | 27-40-02-01 | eClass 9.1 | 27-40-02-01 |
| eClass 10.0 | 27-40-02-01 | UNSPSC     | 31-16-31-02 |

### Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                          |
|--------------------|------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a>     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |
| Engineering Data   | <a href="#">STEP</a>                     |

### Connecting elements H25,0/25

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

