


## Connecting elements H6,0/26D GE

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)



- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code
- other colour code

### General ordering data

|            |                                                   |
|------------|---------------------------------------------------|
| Type       | H6,0/26D GE                                       |
| Order No.  | <a href="#">9019230000</a>                        |
| Version    | Wire-end ferrule, insulated, 20 mm, 18 mm, yellow |
| GTIN (EAN) | 4008190072117                                     |
| Qty.       | 100 pc(s).                                        |
| Packaging  | loose                                             |

## Connecting elements

### H6,0/26D GE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |       |                |            |
|------------|-------|----------------|------------|
| Width      | 26 mm | Width (inches) | 1.024 inch |
| Net weight | 0.5 g |                |            |

### Technical data

|         |           |
|---------|-----------|
| Version | insulated |
|---------|-----------|

### Wire-end ferrules

|                                         |                   |                               |             |
|-----------------------------------------|-------------------|-------------------------------|-------------|
| Collar diameter (D2)                    | 6.3 mm            | Colour code                   | DIN         |
| Conductor cross-section                 | 6 mm <sup>2</sup> | Contact surface diameter (D1) | 3.5 mm      |
| Contact surface length (L2)             | 18 mm             | L1 in mm                      | 26 mm       |
| Metal sleeve thickness (S1)             | 0.2 mm            | Military designation          | T 20A 023 A |
| Plastic collar thickness (S2)           | 0.3 mm            | Stripping length              | 20 mm       |
| Wire connection cross section AWG, max. | AWG 10            |                               |             |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0   | EC000005    |
| eClass 9.0  | 27-40-02-01 | eClass 9.1 | 27-40-02-01 |
| eClass 10.0 | 27-40-02-01 | UNSPSC     | 31-16-31-02 |

### Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                          |
|--------------------|------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a>     |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |
| Engineering Data   | <a href="#">STEP</a>                     |

### Connecting elements H6,0/26D GE

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

## Drawings

### Drawing

