

**Connecting elements  
H0,75/19DS ZH GR****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



For the following conductors: 2 No. 0.75 mm<sup>2</sup> (2 No. AWG 18)

- supplied loose in poly-bag
- Weidmüller colour code
- DIN colour code
- other colour code

**General ordering data**

|            |                                                             |
|------------|-------------------------------------------------------------|
| Type       | H0,75/19DS ZH GR                                            |
| Order No.  | <a href="#">9202830000</a>                                  |
| Version    | Wire-end ferrule, Twin wire-end ferrule, 21 mm, 12 mm, grey |
| GTIN (EAN) | 4032248515776                                               |
| Qty.       | 500 pc(s).                                                  |
| Packaging  | loose                                                       |

## Connecting elements

### H0,75/19DS ZH GR

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |                |            |
|------------|---------|----------------|------------|
| Width      | 20 mm   | Width (inches) | 0.787 inch |
| Net weight | 0.166 g |                |            |

### Technical data

|         |                       |
|---------|-----------------------|
| Version | Twin wire-end ferrule |
|---------|-----------------------|

### Wire-end ferrules

|                                         |        |                             |                      |
|-----------------------------------------|--------|-----------------------------|----------------------|
| Collar height (A)                       | 5.5 mm | Collar width (B)            | 3 mm                 |
| Colour code                             | DIN    | Conductor cross-section     | 0.75 mm <sup>2</sup> |
| Contact surface diameter (D1)           | 1.7 mm | Contact surface length (L2) | 12 mm                |
| L1 in mm                                | 18 mm  | Metal sleeve thickness (S1) | 0.15 mm              |
| Plastic collar thickness (S2)           | 0.3 mm | Stripping length            | 21 mm                |
| Wire connection cross section AWG, max. | AWG 18 |                             |                      |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0   | EC000005    |
| eClass 9.0  | 27-40-02-01 | eClass 9.1 | 27-40-02-01 |
| eClass 10.0 | 27-40-02-01 | UNSPSC     | 31-16-31-02 |

### Approvals

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                    |                                      |
|--------------------|--------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 6 TOOLS 15/16 EN</a> |
| Engineering Data   | <a href="#">WSCAD, EPLAN</a>         |
| Engineering Data   | <a href="#">STEP</a>                 |

**Connecting elements**  
**H0,75/19DS ZH GR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings****Drawing**