



N412 Single Door Flanged Disconnect Ultimate Series 36 X 32 X 8, 304 Stainless Steel

By Wiegmann
Catalog # [N412363208CDSS](#)

N412 Single Door Flanged Disconnect Ultimate Series 36X32X8 304 Stainless Steel.

Application

These general purpose disconnect enclosures accept major brand disconnect switches and circuit breakers, available with or without Wiegmann-supplied defeater door handle and handle hardware.

General

Catalog Number	N412363208CDSS
Color	Brushes Stainless Steel
Construction	Continuously Welded Seams
Cover Type	Door
EU RoHS Indicator	Yes
Finish Type	Smooth Grained Stainless
Knockouts	No
Latches Type	2-Point
Listings	- cULus - IEC 60529
Material	Stainless Steel
Mounting Type	Mounting Holes
Number of Doors (Fixed)	1
Number of Holes	4
Type	Enclosure
UPC	786725862726

Dimensions

Cubic Capacity	9216 cu.in
Depth	8 in
Height	36 in
Weight	98 lb
Width	32 in

Conductor Related



*Representative Image

Cable Entry	NO
-------------	----

Certifications And Compliance

Certification - CSA Approved	NO
Certification - ETL	NO
Certification - cULus	YES
Certified Listed	- cULus - IEC
Industry Standard(s)	- cULus - IEC 60529
Nema Rating	1,3R,12,13,4,4X
UL Listed	Yes

Logistics

Carton Quantity	1
-----------------	---

Product Assets

- [3D Models - N412363208CDSS](#)
- [Brochures - Nema 4X Stainless Steel & Aluminum Enclosures](#)
- [Catalogs - Wiegmann Disconnects](#)
- [Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
- [Engineering Drawing - MOD Center Drawings Instructions](#)
- [Engineering Drawing - N412363208CDSS-MOD](#)
- [Engineering Drawing - HWDN412363208CDSS-S](#)
- [Sales Drawings - HWDN412363208CDSS-S](#)
- [SDS - HCC SDS](#)
- [Specifications - N412363208CDSS Specification Sheet](#)
- [Specifications - N412363208CDSS Specification Sheet French](#)
- [Specifications - N412363208CDSS](#)
- [Terms and Conditions - HCC Terms & Conditions](#)