

N412 Double Door Wall-Mount Ultimate 24X48X08 Stainless Steel

By Wiegmann Catalog # N412D244808SSC

N412 Double Door Wall-Mount Ultimate 24X48X08 Stainless Steel

Features

- Stainless steel construction
- Continuous welded seams
- Doors sealed with poured-in-place gaskets
- Grounding studs welded to doors and body
- Collar studs for mounting optional ULTIMATE series back panels
- 3-point keylocking/padlocking handle included
- NEMA 3R, 4, 4X, 12, 13 and IP66

Application

Hubbell Wiegmann N412DSSC Ultimate Series Disconnects are designed to house and protect electrical and electronic components from harsh, dirty environments. For use in installations where dirt, dust, oil, water, or other contaminants are present.

General

Catalog Number N412D244808SSC Brushes Stainless Steel Color Construction Continuously Welded Seams Door

Cover Type

Smooth Grained Stainless Finish Type

Knockouts

3-Point Handle Latches Type Listings cULus • IEC 60529 Material Stainless Steel

Mounting Type Mounting Holes Number of Doors (Fixed) 2

Number of Holes Ultimate Series Ultimate Series Sub Brand Enclosure Type **UPC** 786725890507



Dimensions

Cubic Capacity	9216 cu.ir
Depth	08 in
Height	24 in
Width	48 in

Conductor Related

Cable Entry NO

Certifications And Compliance

Buy America(n) Qualified Contact Manufacturer NO

Certification - CSA Approved Certification - ETL NO Certification - cULus YES Certified Listed cULus

IEC

Industry Standard(s) cULus

IEC 60529

Nema Rating 1,3R,12,13,4,4X

Logistics

Carton Quantity

Product Assets

3D Models - N412D244808SSC

Catalogs - Section E Stainless Steel & Aluminium Engineering Drawing - HWDN412D244808SSC-S Sales Drawings - HWDN412D244808SSC-S

SDS - HCC SDS

Sell Sheets - N412 ULTIMATE Stainless Steel Series Double Door

Enclosure

Specifications - N412D244808SSC

Terms and Conditions - HCC Terms & Conditions

