

N12 Two Door Floor-Mount Right Flanged Disconnect 72X73X12 Carbon Steel - Gray

By Wiegmann
Catalog # [WA72X7312U](#)



*Representative Image

N12 Two Door Floor-Mount Right Flanged Disconnect 72X73X12
Carbon Steel - Gray

Features

- Designed for indoor use in protecting components from dust, dirt, oil and water
- Punching in right flange (WAXU) or center post (WACPXU) to house the following disconnect operating handles with appropriate adaptor plate: Allen-Bradley Bulletin 1494V, ABB, Cutler-Hammer/Westinghouse type C361 and Type C371, General Electric Type STDA and Spectra Flex, I-T-E Max-Flex, and Square D Class Class9422 variable depth and cable mechanisms.

Application

The Wiegmann universal cutout is used in large freestand and floorstand enclosures.

General

Catalog Number	WA72X7312U
Construction	Continuously Welded Seams
EU RoHS Indicator	No
Finish Type	Polyester Powder
Latches Type	3-Point Padlocking Handle
Material	Carbon Steel
Mounting Type	15 in High Floor Stand Kit
Number of Doors (Fixed)	2
Type	Enclosure
UPC	786725428656

Dimensions

Actual Depth	12.13 in
Actual Height	72.13 in
Actual Width	73.75 in
Depth	12 in
Height	72 in
Weight	710 lb
Width	74 in

Certifications And Compliance

Certified Listed	cULus
Nema Rating	12
UL Listed	Yes

Logistics

Carton Quantity	1
-----------------	---

Product Assets

[3D Models - WA72X7312U](#)
[Catalogs - Section G Disconnects](#)
[Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice](#)
[Engineering Drawing - HWDWA72X7312U-S](#)
[Sales Drawings - HWDWA72X7312U-S](#)
[SDS - HCC SDS](#)
[Specifications - WA72X7312U](#)
[Specifications - WA72X7312U Specification Sheet French](#)
[Specifications - WA72X7312U Specification Sheet English](#)
[Terms and Conditions - HCC Terms & Conditions](#)