

Straight Blade Devices,
Receptacles, Duplex, Heavy Duty
Grade, 2-Pole 3-Wire Grounding,
20A 250V, 6-20R, Ivory

By Hubbell Wiring Device-Kellems
Catalog # 5462IV

Straight Blade Devices, Receptacles, Duplex, Heavy Duty Grade,
2-Pole 3-Wire Grounding, 20A 250V, 6-20R, Ivory

Features

- Back and side wired
- Fed- Spec UL listed
- Smooth nylon face, Brass triple-wipe contacts

Application

Hubbell-Pro Heavy Duty

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #14-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

| | |
|------------------------------|--|
| Catalog Number | 5462IV |
| Color | Ivory |
| EU RoHS Indicator | Contact Manufacturer |
| Horsepower - Maximum | 2 |
| Material - Mounting Hardware | Screw Mounting |
| Number Of Poles | 2-Pole |
| OEM Brand Name | Hubbell Wiring Device-Kellems |
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
| Series | Hubbell-PRO |
| Style | Smooth Face |
| Type | Standard Duplex |
| UPC | 783585555904 |



Dimensions

| | |
|--------|--------|
| Weight | 0.2 lb |
|--------|--------|

Electrical Ratings

| | |
|----------------------------|---------------------------|
| Amperage Rating | 20 A |
| Connectivity | Back and Side Wired |
| Current / Amperage Rating | 20 A |
| Current Rating | 20 A |
| Dielectric Strength | Withstands 2,000V minimum |
| Voltage Rating Description | 250 V |
| Wattage | 5000 W |

Conductor Related

| | |
|-----------------|--------------------|
| Number Of Wires | 3-Wire |
| Wire Size | #14 AWG to #10 AWG |

Certifications And Compliance

| | |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none">• Certified to CSA 22.2, No. 42• Fed. Spec. W-C-596• NEMA® WD-6 Compliant• UL Listed to UL498 File No. E2186 |
| Nema Rating | 6-20R |

Logistics

| | |
|-----------------|----|
| Carton Quantity | 10 |
|-----------------|----|

Product Assets

[Catalog Page - WDK A-28 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - 5462IV AutoCAD Drawing](#)
[Literature - Hubbell-PRO 15A & 20A 250V Duplex Receptacles](#)
[Specifications - 5462IV](#)
[Warranty - Industrial & Commercial Products](#)