

## Circuit Guard® Extra Heavy Duty Hard Wired GFCI with Manual Set, 30A, 240V AC, Black

By Hubbell Wiring Device-Kellems

Catalog # [GFHW23005](#)

Power Protection Products, Hard Wired GFCI,  
Industrial/Commercial, No Output, 30A 240V AC, 4-6 mA Trip  
Level, Black.



### Features

- Electromagnetic Latching Mechanism
- Trips if ground and neutral touch at load side
- Red blinking light plus optional audible alarm
- Open neutral protection Trips upon loss of neutral

### Application

- Wire Into Circuit

### Performance

- Electrical - Dielectric Withstand - 1500 VRMS across contact, 4000 VRMS between conductors & enclosure
- Electrical - Operating Voltage Range - 85% to 110%
- Electrical - Rated Voltage - 120V AC, 240V AC & 120/240V, 3Ø 250V AC, 3Ø 120/208V AC
- Electrical - Surge Withstand - 6000V impulse, 0.5 ms rise time 100kHz ringing frequency
- Environmental - Construction - Industrial grade design
- Environmental - Housing Rating - UL Type 4X
- Environmental - Leakage Current - At 93% Humidity leakage current is zero
- Environmental - Operating Temperature - -35°C to 66°C, -30°F to 150°F.
- Environmental - Type - Class A GFCI

### General

Catalog Number	GFHW23005
Color	Black
Construction	Fabricated
EU RoHS Indicator	No
Item Type	Industrial Grade
Material - Insulation	Thermoplastic
OEM Brand Name	Hubbell Wiring Device-Kellems
Series	Extra Heavy Duty
Specifications	<ul style="list-style-type: none"> <li>• Response Time - .025 sec. Max</li> <li>• Switch Interface - Double Insulated</li> <li>• Trip Level - 4 to 6 mA</li> </ul>

Style	Manual Set
Temperature Rating	-35 Degrees C to 66 Degrees C (-30 Degrees F to 150 Degrees F)
Type	Hard Wired
UPC	783585005218

### Dimensions

Weight	1.6 lb
--------	--------

### Electrical Ratings

Amperage Rating	30 A
Connectivity	Hard Wired
Current / Amperage Rating	30 A
Current Rating	30 A
Voltage Rating	240 VAC
Voltage Rating Description	240 VAC

### Conductor Related

Conductor Size	#10 AWG
Conductor Type	Copper
Number of Conductors	3
Strands	Multi

### Certifications And Compliance

Industry Standard(s)	UL Listed
----------------------	-----------

### Logistics

Carton Quantity	5
-----------------	---

### Product Assets

Catalog Page - <a href="#">WDK K-18 Catalog Page</a>
Catalogs - <a href="#">WDK Catalog Full 2024</a>
Engineering Drawing - <a href="#">GFHW23005 AutoCAD Drawing</a>

[Installation Manuals - WIRING\\_PD1827\\_INSTALLINST](#)

[Literature - Safety Product Guide](#)

[Literature - 20A & 30A GFCI Protected Cord Drops](#)

[Literature - PULP & PAPER SOLUTIONS](#)

[Literature - Pulp & Paper Solutions](#)

[Sales Drawings - WDK\\_GFHW23\\_DRAWING\\_PDF](#)

[Specifications - GFHW23005](#)

[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved  
WDK-GFHW23005-SPEC-EN | REV 1/2025