

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male, Plug, 60A 125/250V, 3-Pole 4-Wire Grounding, Watertight-Reversed Service

By Hubbell Wiring Device-Kellems

Catalog # [HBL460P12WR](#)

Heavy Duty Products, IEC Pin and Sleeve Devices, Industrial Grade, Male, Plug, 60A 125/250V, 3-Pole 4-Wire Grounding, Terminal Screws, Orange, Watertight- Reversed Service

Features

- Gasketed sealing ring provides watertight seal
- Heavy duty external cord grips

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 3,000V AC Min
- Electrical - Max. Working Voltage - 600V AC RMS
- Environmental - Flammability - HB or Better per UL 94 or CSA C22.2 No. 0.17
- Environmental - Ingress Protection - IP67 Suitability
- Environmental - Moisture Resistance - Watertight per IEC 60309-1
- Environmental - Operating Temperature - Maximum Continuous 75°C
- Minimum - 40°C w/o impact
- Mechanical - Impact Resistance - Per CSA C22.2 No. 182.1 / UL1682
- Mechanical - Product Identification - Identification and ratings are a permanent part of the device housing.
- Mechanical - Terminal Identification - Terminals identified in accordance with North American and IEC conventions

General

Catalog Number	HBL460P12WR
Color	Orange
EU RoHS Indicator	Yes
Environmental Conditions	Watertight
Item Type	Male Plug- Reversed
Material	Composite
Material - Mounting Hardware	Cord Mounted
Number Of Poles	3-Pole
OEM Brand Name	Hubbell Wiring Device-Kellems
Series	Non-Fused
Specifications	<ul style="list-style-type: none">• Contact Carrier - High-Impact Thermoset



- Housing - Zytel® ST801 Nylon
- Locking Ring - Reinforced Thermoplastic Polyester
- Retainer - High-Impact Thermoset
- Terminal Screws - Stainless Steel

Reverse Service
Watertight Mating Plug
783585012728

Style

Type
UPC

Dimensions

Display Size
Standard Sized

Electrical Ratings

Amperage Rating	60 A
Connectivity	Pressure Terminal Screws
Current / Amperage Rating	60 A
Current Rating	60 A
Phase	Single Phase
Voltage Rating	120/240 VAC
Voltage Rating Description	120/240 VAC

Conductor Related

Cord Type	All Portable
Number Of Wires	4-Wire
Wire Size	#8 AWG to #2 AWG

Certifications And Compliance

Industry Standard(s)

- CSA Standard C22.2 No. 182.1
- UL Classified to IEC60309-1
- UL Listed, File E146032

Nema Rating
Non-NEMA

Logistics

Carton Quantity 10

Product Assets

[Catalog Page - WDK G-22 Catalog Page](#)

[Catalogs - WDK Catalog Full 2024](#)

[Engineering Drawing - HBL460P12WR AutoCAD Drawing](#)

[Installation Manuals - WIRING_PD1303_INSTALLINST](#)

[Literature - PULP & PAPER SOLUTIONS](#)

[Literature - IEC Pin & Sleeve Devices](#)

[Literature - Pulp & Paper Solutions](#)

[Sales Drawings - WDK_HBL460P_DRAWING_PDF](#)

[Specifications - HBL460P12WR](#)

[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved

WDK-HBL460P12WR-SPEC-EN | REV 1/2025