

UL 1686 C1 Pin and Sleeve

60A, 600/250V AC/DC, 3 Pole, 4 Wire

## Reversed Service Insulgrip® Plug

# HUBBELL

### Features

- Beryllium copper spring maintains high unit pressure on mating sleeves
- Locking ring provides UL Type 4X watertight, dust-tight seal
- Catalog number and rating visible while in use
- Pin chamber confines arcing within the interior chamber



### Ordering Information

Description	UPC	Catalog Number
Watertight Insulgrip Plug, Reversed Service	783585012438	HBL460PS2WR
Device Color	Grounding Style	
Aluminum	Style 2	

### Standards


UL Standard 1682, UL 50, and UL 1010

CSA Certified to CSA Spec. C22.2 No. 159

UL Listed and CSA Certified Type 4X

### Specifications

Housing	Valox® 357
Plug Shroud	Aluminum
Clamp Nut	Nickel Plated Brass
Gland Cap	Rynite® SST35
Retainer	Thermoset Polyester
O-Ring, Gaskets & Seals	Neoprene



### Performance

#### Electrical

Current Interrupting Certified for current interrupting at full rated current

Dielectric Voltage Withstands 3,000V AC  
Max. Working Voltage 600V AC RMS

#### Mechanical

Impact Resistance Per CSA C22.2, No. 182.1, UL 1682  
Product Identification Identification and ratings are permanently fastened to the device housing  
Terminal Identification Terminals identified in accordance with UL 1686(1, 2, 3, Green)

#### Environmental

Flammability (Enclosure) UL 94V-0 and CSA C22.2 No. 0.17  
Moisture Resistance Type 3, 4, 4X per UL 50E and CSA 22.2, No. 94  
Operating Temperatures Max. Continuous 75°C; Min. -40°C w/o impact -25° with impact

### Online Resources

Customer Use Drawing  
eCatalog  
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.