## HUBBELL Wiring Device-Kellems

# **Surge Protective Devices, SPIKESHIELD TVSS Duplex** Receptacle with Light, 15A 125V, 5-15R, White

By Hubbell Wiring Device-Kellems Catalog # HBL5260WSA

Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle with Light, 15A 125V, 5-15R, White

#### **Features**

- Automatic self-grounding staple
- · Distinctive surge symbol provides quick identification
- Power-on indicator light verifies that power is available
- · Alert alarm sounds when surge protection is no longer functioning

## **Application**

**Decorator Duplex** 

#### Performance

- Electrical Protection Modes Normal and Common Modes
- Electrical Response Time Approximately 5 ns
- Electrical Transient Suppression Peak Energy (10 X 100 Qs), Peak Current (8 X 20 Qs)
- Electrical Voltage 120V AC + 10% 15%
- Environmental Flammability UL 94V-2
- Environmental Operating Temperature 32°F to 140°F (0°C to 60°C)

#### General

HBL5260WSA Catalog Number

Color White **EU RoHS Indicator** 

**Environmental Conditions** Indoor Dry Unless Protected By

Additional Means

Indicator(s) Type None

Surge Protection Receptacles Item Type

Material Composite Material - Mounting Hardware **Mounting Screws** 

**OEM Brand Name Hubbell Wiring Device-Kellems** 

32 Deg F to 140 Deg F (O Deg Operating Temperature C to 60 Deg C)

Outlet Straight Blade

Response Time

Specification Grade Series Specifications · Base Material - Nvlon

• Contact Design - Tandem

**Modified Bypass** 

· Face Material - Nylon



 Mounting Strap - .050" (1.3) Steel-Zinc Coated

• Power Contact - .031" (.8)

Туре Duplex **UPC** 783585219905

#### **Dimensions**

Display Size Standard

### **Electrical Ratings**

Amperage Rating 15 A

Connectivity Terminal Screws

Current / Amperage Rating 15 A Current Rating 15 A 60 Hz Frequency Rating Phase Single Phase

Voltage Rating 125 V Voltage Rating Description 125 V

## **Certifications And Compliance**

Industry Standard(s) · CSA Certified to

Specification C22.2 No. 42

• Listed to UL Standards 498

UL Listed File E2186

Nema Rating 5-15R

# Logistics

Carton Quantity 10

## **Product Assets**

Catalog Page - WDK M-13 Catalog Page

Catalogs - WDK Catalog Full 2024

Engineering Drawing - HBL5260WSA AutoCAD Drawing

Installation Manuals - WIRING\_PD1152\_INSTALLINST

Literature - Residential Catalog

Literature - Residential Product Guide

Sales Drawings - WDK HBL5260 DRAWING PDF

Specifications - HBL5260WSA



©2025 Hubbell Incorporated. All rights reserved WDK-HBL5260WSA-SPEC-EN | REV 1/2025