

Surge Protective Devices,
SPIKESHIELD TVSS Duplex
Receptacle with Light, 20A 125V, 5-
20R, Ivory

By Hubbell Wiring Device-Kellems
Catalog # [HBL5360ISA](#)



Surge Protective Devices, SPIKESHIELD TVSS Duplex Receptacle
with Light, 20A 125V, 5-20R, Ivory

Features

- Automatic self-grounding staple
- Distinctive surge symbol provides quick identification
- Power-on indicator light verifies that power is available
- Alert alarm sounds when surge protection is no longer functioning

Application

Decorator Duplex

Performance

- Electrical - Protection Modes - Normal and Common Modes
- Electrical - Response Time - Approximately 5 ns
- Electrical - Transient Suppression - Peak Energy (10 X 100 Qs), Peak Current (8 X 20 Qs)
- Electrical - Voltage - 120V AC + 10% - 15%
- Environmental - Flammability - UL 94V-2
- Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

General

| | |
|------------------------------|---|
| Catalog Number | HBL5360ISA |
| Color | Ivory |
| EU RoHS Indicator | No |
| Environmental Conditions | Indoor Dry Unless Protected By Additional Means |
| Indicator(s) Type | LED and Audible Alarm |
| Item Type | Surge Protection Receptacles |
| Material | Composite |
| Material - Mounting Hardware | Mounting Screws |
| OEM Brand Name | Hubbell Wiring Device-Kellems |
| Operating Temperature | 32 Deg F to 140 Deg F (0 Deg C to 60 Deg C) |
| Outlet | Straight Blade |
| Response Time | 5 |
| Series | Specification Grade |
| Specifications | <ul style="list-style-type: none">• Base Material - Nylon• Contact Design - Tandem Modified Bypass• Face Material - Nylon |

- Mounting Strap - .050" (1.3) Steel-Zinc Coated
- Power Contact - .031" (.8) Brass

| | |
|------|--------------|
| Type | Duplex |
| UPC | 783585060217 |

Dimensions

| | |
|--------------|----------|
| Display Size | Standard |
|--------------|----------|

Electrical Ratings

| | |
|----------------------------|-----------------|
| Amperage Rating | 20 A |
| Connectivity | Terminal Screws |
| Current / Amperage Rating | 20 A |
| Current Rating | 20 A |
| Frequency Rating | 60 Hz |
| Phase | Single Phase |
| Voltage Rating | 125 V |
| Voltage Rating Description | 125 V |

Certifications And Compliance

| | |
|----------------------|---|
| Industry Standard(s) | <ul style="list-style-type: none">• CSA Certified to Specification C22.2 No. 42• Listed to UL Standards 498• UL Listed File E2186 |
| Nema Rating | 5-20R |

Logistics

| | |
|-----------------|------|
| Carton Quantity | 10 |
| Pallet Quantity | 3500 |

Product Assets

[Catalog Page - WDK M-13 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - HBL5360ISA AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD1152_INSTALLINST](#)
[Literature - SpikeShield® Power Quality Surge Protective Devices](#)
[Sales Drawings - WDK_HBL5360_DRAWING_PDF](#)



A Hubbell brand