

Surge Protective Devices,  
SPIKESHIELD TVSS Plug Strips, 6)  
Receptacles, Metallic Body, 1050  
Joules, 6' Cord

By Hubbell Wiring Device-Kellems  
Catalog # [HBL6MPS1050](#)

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 6)  
Receptacles, Metallic Body, 1050 Joules, 6' Cord

Features

- Office White color for aesthetics and metal housing
- 1050 joule rating
- 6 foot cord
- wire management

Application

Standard Devices

Performance

- Electrical - Max Surge Current - 19.5kA
- Electrical - Max. Operating Voltage - 130
- Electrical - Operating Frequency - 50/60Hz
- Environmental - Operating Temperature - -40°F to 160°F (-40°C to 70°C)

General

|                              |                                                 |
|------------------------------|-------------------------------------------------|
| Catalog Number               | HBL6MPS1050                                     |
| Color                        | Office White                                    |
| EU RoHS Indicator            | Yes                                             |
| Environmental Conditions     | Indoor Dry Unless Protected By Additional Means |
| Indicator(s) Type            | LED Indicator                                   |
| Item Type                    | Surge Protection Plug Strips                    |
| Material                     | Steel                                           |
| Material - Mounting Hardware | Portable                                        |
| Number Of Outlets            | 6                                               |
| OEM Brand Name               | Hubbell Wiring Device-Kellems                   |
| Operating Temperature        | 32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)     |
| Outlet                       | Straight Blade 5-15R                            |
| Response Time                | 5                                               |
| Series                       | Economy Surge Strips                            |



Specifications

- Color - Off. White
- Height - 1.5" (38.1)
- Housing - Metal
- Length - 12.25" (311.2)
- Width - 2.5" (63.5)

Type  
UPC

Metallic  
783585120676

Dimensions

Display Size 1050 Joules

Electrical Ratings

|                           |              |
|---------------------------|--------------|
| Connectivity              | Plug-In      |
| Current / Amperage Rating | 15 A         |
| Current Rating            | 15 A         |
| Frequency Rating          | 60 Hz        |
| Phase                     | Single Phase |

Conductor Related

Cord Length 6 ft

Logistics

|                 |     |
|-----------------|-----|
| Carton Quantity | 20  |
| Pallet Quantity | 400 |

Product Assets

- [Catalog Page - WDK M-9 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Installation Manuals - WIRING\\_PD2380\\_INSTALLINST](#)
- [Literature - SpikeShield® Power Quality Surge Protective Devices](#)
- [Specifications - HBL6MPS1050](#)
- [Warranty - Surge Plug Strips](#)