Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A 125V, 7 Oulet, 150 Joules, 15' Cord, Office White

By Hubbell Wiring Device-Kellems
Catalog # HBL7PS105015A

Surge Protective Devices, SPIKESHIELD TVSS Plug Strips, 15A 125V, 7 Oulet, 150 Joules, 15' Cord, Office White

Features

- 1050 joule, 6 foot cord, $5,000 down-line warranty
- Tamper tamper resistant shutters.

Application

7 Outlet, Standard Devices

Performance

- Electrical - Max Surge Current - 19.5kA
- Electrical - Max. Operating Voltage - 130
- Electrical - Operating Frequency - 50/60Hz
- Environmental - Operating Temperature - -40°F to 160°F (-40°C to 70°C)

General

Catalog Number	HBL7PS105015A
Color	Office White
EU RoHS Indicator	Yes
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED Indicator
Item Type	Surge Protection Plug Strips
Material	Non-Metallic
Material - Mounting Hardware	Portable
Number Of Outlets	7
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade 5-15R
Response Time	5
Series	Economy Surge Strips
Specifications	

- Color - Off. White
- Height - 1.85" (47.0)
- Housing - ABS
- Length - 14.75" (374.7)
- Width - 2.36" (59.9)

Type	Non-Metallic
UPC	783585120560

Dimensions

Display Size	1050 Joules

Electrical Ratings

Connectivity	Plug-In
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase

Conductor Related

Cord Length	6 ft

Logistics

Carton Quantity	12
Pallet Quantity	420

Product Assets

Catalog Page - WDK M-9 Catalog Page
Catalogs - WDK Catalog Full 2024
Engineering Drawing - HBL7PS105015A AutoCAD Drawing
Installation Manuals - WIRING_PD2380_INSTALLINST
Literature - SpikeShield® Power Quality Surge Protective Devices
Sales Drawings - WDK_HBL7PS105015A_DRAWING_PDF
Specifications - HBL7PS105015A
Warranty - Surge Plug Strips