

## EdgeConnect™, Duplex Receptacle, 20A 125V, 5-20R, Screwless Terminal, Brown

By Hubbell Wiring Device-Kellems  
Catalog # [HBL8300ST](#)

Straight Blade Devices, EdgeConnect™, Duplex Receptacle, Hospital Grade, 2-Pole 3-Wire, 20A 125V, 5-20R, Screwless Terminal, Brown



### Features

- Back wired screwless termination for faster termination time
- No need for screwdriver and torque wrench
- Spring Termination eliminates strand relaxation
- Triple and Double Wipe Contacts
- Easy access split circuit tab

### Application

Heavy Duty

### General

Catalog Number	HBL8300ST
Color	Brown
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Item Type	Receptacle
Material	Thermoplastic/C
Mounting Type	Screw Mount
Number Of Poles	2-Pole
Series	EdgeConnect™
Size	Standard Sized Product
Style	Finder Groove Face
Temperature Rating	Maximum continuous 75°C; minimum -40°C (w/o impact)
Type	Hospital Grade
UPC	783585687384

### Electrical Ratings

Current / Amperage Rating	20 A
Dielectric Strength	Withstands 2,000V minimum

Phase Single  
Voltage Rating 125 V

### Conductor Related

Number Of Wires 3-Wire  
Wire Size #14 AWG to #10 AWG

### Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none"><li>• UL Listed to UL498 File No. E2186</li><li>• Certified to CSA 22.2, No. 42 File 285</li><li>• Fed. Spec. W-C-596, NEMA® WD-6 Compliant</li></ul>
Nema Rating	5-20R

### Logistics

Carton Quantity 10

### Product Assets

- [3D Product View - WDK\\_DuplexReceptacles](#)
- [Catalog Page - WDK A-19 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Installation Manuals - PD3029](#)
- [Literature - EdgeConnect™ Technology FAQ](#)
- [Literature - Electrical Products - Healthcare Solutions](#)
- [Literature - EdgeConnect™ Technology](#)
- [Literature - EdgeConnect™ Termination vs Standard Push Wire](#)
- [Sales Drawings - M14623](#)
- [Specifications - HBL8300ST](#)
- [Warranty - Industrial & Commercial Products](#)