

Disconnect Switches, Sloped
Enclosure, 30A 600V AC, Non-
Fused, NEMA 4X, Stainless Steel,
With 5' Pre-Wired Female Cable

By Hubbell Wiring Device-Kellems
Catalog # [HBLDS3SSRMQ5](#)

Disconnect Switches, Sloped Enclosure, 30A 600V AC, Non-
Fused, NEMA 4X, Stainless Steel, With 5' Pre-Wired Female
Cable

Features

- Sloped Enclosure
- 30A 600V AC
- Non-Fused
- NEMA 4X

Performance

- Electrical - Dielectric Voltage - 2,200V AC minimum for 1 minute
- Electrical - Electrical Life - 6,000 cycles with load
- Electrical - Max. Working Voltage - 600V AC RMS
- Environmental - Flammability - UL94-5VA and V0 Classification
- Environmental - Operating Temperature - Max. continuous 75°C, Min. continuous -40°C
- Mechanical - Impact Resistance - UL746C
- Mechanical - Mechanical Life - 10,000 minimum cycles
- Mechanical - Terminal Accommodations - 30A, #14 AWG Min. - #10 AWG Max
- Mechanical - Terminal Torque - 30A, 20 inch pounds

General

Catalog Number	HBLDS3SSRMQ5
EU RoHS Indicator	Contact Manufacturer
Enclosure Type	Type 4X
Horsepower - Maximum	15
Ingress Protection	IP67
Operating Temperature	Maximum continuous 75°C and minimum -40°C without Impact
Series	MotorQuick/LINKOSITY
Type	Disconnect Switches
UPC	783585541570

Dimensions

Dimensions	8.5 in x 6 in x 4.12 in
Height	4.12 in
Length	8.5 in



Width	6 in
-------	------

Electrical Ratings

Amperage Rating	30 A
Connectivity	Pre-Wired
Current Rating	30 A
Dielectric Strength	2,200V AC minimum for 1 minute
Phase	Three Phase

Conductor Related

Wire Size	#14 AWG to #10 AWG
-----------	--------------------

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none">• Listed to UL 2238 and UL 50E• UL 508, Industrial Control Equipment File #E36355
----------------------	--

Product Assets

- [Catalog Page - WDK F-19 Catalog Page](#)
- [Catalog Page - WDK F-17 Catalog Page](#)
- [Catalog Page - WDK F-11 Catalog Page](#)
- [Catalog Page - WDK I-8 Catalog Page](#)
- [Catalog Page - WDK F-13 Catalog Page](#)
- [Catalogs - WDK Catalog Full 2024](#)
- [Literature - Safety Product Guide](#)
- [Literature - Labelless Disconnects](#)
- [Literature - Food Processing Guide](#)
- [Literature - PULP & PAPER SOLUTIONS](#)
- [Literature - Pulp & Paper Solutions](#)
- [Literature - Wiring Device Solutions for Strategic Manufacturing Facilities](#)
- [Literature - Linkosity Wiring System](#)
- [Sales Drawings - M12747](#)
- [Specifications - HBLDS3SSRMQ5](#)
- [Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
WDK-HBLDS3SSRMQ5-SPEC-EN | REV 1/2025