

Hospital Grade Surge Suppression
Receptacle, Isolated Ground, 15A
125V, 5-15R, Orange

By Hubbell Wiring Device-Kellems
Catalog # [IG8262OSA](#)

Hospital Grade Surge Suppression Receptacle, Isolated Ground,
15A 125V, 5-15R, Orange

Features

- High-impact nylon face resists breakage
- Automatic grounding clip attached to bridge
- Power-on indicator light verifies instantly that power is available
- Distinctive surge symbol for visual identification of surge suppression receptacle

Application

- Decorator Duplex with Light and Alarm

Performance

- Electrical - Frequency - 60Hz
- Electrical - Protection Modes - Normal and Common Modes
- Electrical - Response Time - Approximately 5 ns
- Electrical - Transient Suppression - Peak Energy (10 X 100 Qs)
Peak Current (8 X 20 Qs)
- Electrical - Voltage - 120V AC + 10% - 15%
- Environmental - Flammability - UL 94V-2
- Environmental - Operating Temperature - 32°F to 140°F (0°C to 60°C)

General

Catalog Number	IG8262OSA
Color	Orange
EU RoHS Indicator	No
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Indicator(s) Type	LED and Audible Alarm
Item Type	Surge Protection Receptacles
Material	Composite
Material - Mounting Hardware	Mounting Screws
OEM Brand Name	Hubbell Wiring Device-Kellems
Operating Temperature	32 Deg F to 140 Deg F (0 Deg C to 60 Deg C)
Outlet	Straight Blade
Response Time	5
Series	Hospital Grade
Specifications	<ul style="list-style-type: none">• Base Material - Nylon• Contact Design - Tandem Modified Bypass



- Face Material - Nylon
 - Mounting Screws - Steel-Zinc Plated
 - Power Contacts - .031" (.8) Brass
- Isolated Ground
Duplex
783585060897

Style
Type
UPC

Dimensions

Display Size Standard

Electrical Ratings

Amperage Rating	15 A
Connectivity	Terminal Screws
Current / Amperage Rating	15 A
Current Rating	15 A
Frequency Rating	60 Hz
Phase	Single Phase
Voltage Rating	125 V
Voltage Rating Description	125 V

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none">• CSA Certified to Specification C22.2 No. 42• Listed to UL Standards 498 Receptacles• UL Listed File E2186
Nema Rating	5-15R

Logistics

Carton Quantity 10

Product Assets

[Catalog Page - WDK M-13 Catalog Page](#)
[Catalog Page - WDK L-16 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Engineering Drawing - IG8262OSA AutoCAD Drawing](#)
[Installation Manuals - WIRING_PD1152_INSTALLINST](#)
[Literature - SpikeShield® Power Quality Surge Protective Devices](#)

