#### HUBBELL Wiring Device-Kellems

# Hospital Grade Surge Suppression Receptacle, 20A 125V, 5-20R, Grange

By Hubbell Wiring Device-Kellems Catalog # IG8362RSA

Hospital Grade Surge Suppression Receptacle, 20A 125V, 5-20R, Grange

#### **Features**

- High-impact nylon face resists breakage
- · Automatic grounding clip attached to bridge
- Power-on indicator light verifies instantly that power is available
- Distinctive surge symbol provides quick visual identification of surge suppression receptacle

### Application

· Decorator Duplex with Light and Alarm

#### Performance

- Electrical Frequency 60Hz
- Electrical Protection Modes Normal and Common Modes
- Electrical Response Time Approximately 5 ns
- Electrical Transient Suppression Peak Energy (10 X 100 Qs)
   Peak Current (8 X 20 Qs)
- Electrical Voltage 120V AC + 10% 15%
- Environmental Flammability UL 94V-2
- Environmental Operating Temperature 32°F to 140°F (0°C to 60°C)

#### General

Outlet

Catalog Number IG8362RSA
Color Red
EU RoHS Indicator No

Environmental Conditions Indoor Dry Unless Protected By

Additional Means

Indicator(s) Type

LED and Audible Alarm

Item Type

Surge Protection Receptacles

Material

Composite

Material Composite

Material - Mounting Hardware Mounting Screws

OEM Brand Name Hubbell Wiring Device-Kellems
Operating Temperature 32 Deg F to 140 Deg F (0 Deg

C to 60 Deg C) Straight Blade

Response Time

eries Hospital Grade

Specifications • Base Material - Nylon

 Contact Design - Tandem Modified Bypass



• Face Material - Nylon

• Mounting Screws - Steel-

Zinc Plated

• Power Contacts - .031" (.8)

Brass

Style Isolated Ground

Type Duplex

UPC 783585060958

#### **Dimensions**

Display Size Standard

#### **Electrical Ratings**

Amperage Rating 20 A

Connectivity Terminal Screws

Current / Amperage Rating20 ACurrent Rating20 AFrequency Rating60 HzPhaseSingle Phase

Voltage Rating 125 V Voltage Rating Description 125 V

# **Certifications And Compliance**

Industry Standard(s) • CSA Certified to

Specification C22.2 No. 42

Listed to UL Standards 498
 Receptacles

UL Listed File E2186

Nema Rating 5-20R

#### Logistics

Carton Quantity 10

## **Product Assets**

Catalog Page - WDK M-13 Catalog Page Catalog Page - WDK L-16 Catalog Page Catalogs - WDK Catalog Full 2024

Engineering Drawing - IG8362RSA AutoCAD Drawing Installation Manuals - WIRING\_PD1152\_INSTALLINST Literature - SpikeShield® Power Quality Surge Protective

Devices



©2025 Hubbell Incorporated. All rights reserved WDK-IG8362RSA-SPEC-EN | REV 1/2025