

H038CNK -- Liquidtight System



Straight Male

Kellems Grips for UL Type A, non-metallic, flexible, liquidtight conduit are available in straight and 90° male and feature a high quality Hubbell plated steel or malleable iron fitting, complete with a sealing O-ring, lock nut and stainless steel mesh.

Product Specifications	
Product Type	Liquidtight System
Liquidtight System Type	Flexible Non-Metallic Liquidtight Conduit Grip Type A
Liquidtight Connector Body Style	Straight
Trade Size	3/8"
Operating Temperature	-30°F to +225°F (-34°C to +107°C)
Mesh Grip Flammability Rating	UL 94-HB
Fitting Flammability Rating	UL 94-V2
Recommended Knockout Hole Size	.859 to .906 (2.18 - 2.30)
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2.
Mesh Length	3 3/4" (9.52)
Dimension A	1.875" (4.76)
Dimension B	.547" (1.39)
Dimension C	1.156" (2.94)
Dimension D	3.75" (9.52)
Certifications	UL Listed CSA Certified
UPC Number	78358533478
Weight in LBs	0.2
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

