

# H200CNK -- Liquidtight System



Straight Male

Kellems Grips for UL Type A, non-metallic, flexible, liquidtight conduit are available in straight and 90° male and feature a high quality Hubbell plated steel or malleable iron fitting, complete with a sealing O-ring, lock nut and stainless steel mesh.

## Product Specifications

<b>Product Type</b>	Liquidtight System
<b>Liquidtight System Type</b>	Flexible Non-Metallic Liquidtight Conduit Grip Type A
<b>Liquidtight Connector Body Style</b>	Straight
<b>Trade Size</b>	2"
<b>Operating Temperature</b>	-30°F to +225°F (-34°C to +107°C)
<b>Mesh Grip Flammability Rating</b>	UL 94-HB
<b>Fitting Flammability Rating</b>	UL 94-V2
<b>Recommended Knockout Hole Size</b>	2.453 to 2.500 (6.23 - 6.35)
<b>Hazardous Locations</b>	Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2.
<b>Mesh Length</b>	14 1/2" (36.83)
<b>Dimension A</b>	2.312" (5.87)
<b>Dimension B</b>	.656" (1.67)
<b>Dimension C</b>	3.187" (8.09)
<b>Dimension D</b>	14.50" (36.83)
<b>Certifications</b>	UL Listed CSA Certified
<b>UPC Number</b>	78358533484
<b>Weight in LBs</b>	2.75
<b>Link to Drawing Library</b>	<a href="#">Click here for Library</a>
<b>Link to PDF Catalog</b>	<a href="#">Click here for Catalog</a>

