

EdgeConnect™, Straight Blade Devices, Connector, Industrial/Commercial Grade, 2- Pole 3-Wire Grounding, 20A 125V, 5-20R, Black

By Hubbell Wiring Device-Kellem

Catalog # [HBL5369CBKST](#)

EdgeConnect™, Straight Blade Devices, Connector,
Industrial/Commercial Grade, 2-Pole 3-Wire Grounding, 20A
125V, 5-20R, Black



Features

- Spring termination for a faster and more secure terminal connection
- Ribbed housing is impact and chemical resistant
- Superior cord grip design protects terminations from excess strain
- Accepts #14 - #10AWG, solid or stranded

Application

Extra Heavy Duty Industrial/Commercial Grade

Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current
- Electrical - Dielectric Voltage - Withstands 2,000V minimum
- Environmental - Flammability - UL 94 V-2
- Environmental - Operating Temperatures - Maximum continuous 75°C, minimum -40°C (w/o impact)
- Mechanical - Product Identification - Ratings are a permanent part of the device
- Mechanical - Terminal Accommodation - #12-#10 AWG copper stranded or solid conductor only
- Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 and CSA

General

Catalog Number	HBL5369CBKST
Color	Black
Cord Range	0.230"-0.720"(5.8-18.3)
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Indoor Dry Unless Protected By Additional Means
Horsepower - Maximum	1
Insulation	Insulated Body
Item Type	Insulgrip® Connector
Material	Nylon
Material - Mounting Hardware	Cord Mounted

Number Of Poles
Operating Temperature

2-Pole
Maximum continuous 75°C and minimum -40°C without Impact

EdgeConnect™
Series
Size
Specifications

EdgeConnect™
Style
Size
Body - Nylon, Retainer - Polycarbonate, Cover - Nylon, Cord Clamp - Nylon, Contact - Copper Alloy, Spring - Stainless Steel, Plunger - Nylon, Drive/Assembly/Cord Clamp Screws - Steel

Standard
Temperature Rating

Standard
Maximum continuous 75°C; minimum -40°C (w/o impact)

Connectors
Type
UPC

Connectors
783585965413

Dimensions

Display Size
Weight

Standard Sized Product
0.2 lb

Electrical Ratings

Connectivity
Current / Amperage Rating
Dielectric Strength
Phase
Voltage Rating

Spring Termination
20 A
Withstands 2,000V minimum
Single Phase
125 V

Conductor Related

Conductor Range
Cord Type
Number Of Wires
Number of Conductors
Wire Size

#14 AWG to #10 AWG
All Listed Portables
3-Wire
3-Wire Grounding
#14 AWG to #10 AWG

Certifications And Compliance

Industry Standard(s)	<ul style="list-style-type: none">• CSA Certified to C22.2 No. 42 File 280• Fed. Spec. W-C596G• NEMA® WD-6 Compliant	Catalog Page - WDK A-39 Catalog Page Catalogs - WDK Catalog Full 2024 Installation Manuals - PD3069_Installation Manual Literature - EdgeConnect™ Technology FAQ Literature - EdgeConnect™ Technology Literature - EdgeConnect™ Termination vs Standard Push Wire Sales Drawings - M14757 Specifications - HBL5369CBKST Warranty - Industrial & Commercial Products
Nema Rating	5-20P	
Logistics		
Carton Quantity	10	

Product Assets



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
WDK-HBL5369CBKST-SPEC-EN | REV 3/2025