

HBLALU3800 Series

| HBLALU3800 Series | Description | Color | Catalog Number | Description | Color | Catalog Number |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|----------------|---------------------------------------------------------|
| | Single Channel Base Satin anodized finish. Packed 40 ft. (12.19m) per carton, 10 ft. (3m) lengths. Assembled cover and base dimensions. W: 3.00" (76.20) H: 2.25" (57.15) | Anodized White | HBLALU3800B10 HBLALU3800B10W A: 2.10" (53.34) B: 3.00" (76.20) | Cover Satin anodized finish. Packed 40 ft. (12.19m) per carton, 5 ft. (1.5m) lengths. | Anodized White | HBLALUC5 HBLALUC5W A: 3.00" (76.20) |

| Elbows and Tees | Description | Color | Catalog Number | Description | Color | Catalog Number |
|-----------------|---------------------------------------------------------------------------|----------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------------------------------------------------------------------------|
| | Internal Elbow For making a 90° internal turn in a raceway run. | Anodized White | HBLALU3817* HBLALU3817W* A: 6.00" (152.40) B: 6.00" (152.40) | Inverted Internal Elbow For connecting a vertical run of HBLALU3800 with a horizontal run with its cover facing up. | Anodized White | HBLALU3817N* HBLALU3817NW* A: 6.00" (152.40) B: 5.98" (151.89) |
| | External Elbow For making a 90° external turn in a raceway run. | Anodized White | HBLALU3818* HBLALU3818W* A: 6.00" (152.40) B: 6.00" (152.40) | Tee For branch connections of two runs of HBLALU3800 Raceway. | Anodized White | HBLALU3815* HBLALU3815W* A: 6.00" (152.40) B: 6.00" (152.40) |
| | Flat Elbow For making a 90° flat turn in a raceway run. | Anodized White | HBLALU3811* HBLALU3811W* A: 6.00" (152.40) B: 6.00" (152.40) | | | |

| End Fittings | Description | Color | Catalog Number | Description | Color | Catalog Number |
|--------------|----------------------------------------------------------------------------------------------------|----------------|-------------------------------------------------------------------------------------|---------------------------------------------------------|----------------|-----------------------------------------------------------------------------------|
| | Entrance End Fitting For feeding raceway, has concentric ½ in. and ¾ in. trade size KOs. | Anodized White | HBLALU3810B1 HBLALU3810B1W A: 3.00" (76.20) B: 2.31" (58.74) | Blank End Fitting For closing end of raceway. | Anodized White | HBLALU3810B HBLALU3810BW A: 3.00" (76.20) B: 2.31" (58.74) |

| Fittings | Description | Color | Catalog Number | Description | Color | Catalog Number |
|----------|--------------------------------------------------------------------------------------------------------------------|-------------------|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|-------------------|----------------------------------------------------------|
| | Cover Clip To cover seam where lengths of HBLALU3800 Raceway come together. | Stainless White | HBLALU3806 HBLALU3806W A: 1.38" (34.92) | Wire Clip For holding conductors in place. Can be used for either HBLALU3800 or HBLALU4800 Raceway. | Anodized Aluminum | HBLALUWC A: 1.00" (25.40) |
| | Internal Corner Coupling For butting two raceway sections to form an internal 90° turn in a raceway run. | Anodized Aluminum | HBLALU17A A: 4.00" (101.80) B: 2.00" (50.83) | Grounding Adapter For connection of equipment grounding. #10-32 Locking screws included. | Galvanized Steel | HBLALU09 A: 4.00" (101.80) B: 2.00" (50.83) |

Couplings (Pair)
 To join lengths of HBLALU3800 or HBLALU4800 base.

Note: *HBLALU01 couplings included.
 See page T-40 for cover plates.

Dimensions in Inches (mm)