

Industrial Grade, Motor Disconnect,  
Unfused Switch, Non-Metallic  
Sloped Version Replacement Cover  
for 100A - HBLDS100 and  
HBLDS100T Series

By Hubbell Wiring Device-Kellems  
Catalog # [HBLDS100RC](#)



Industrial Grade, Motor Disconnect, Unfused Switch, Non-Metallic  
Sloped Replacement Cover for 100A Version, HBLDS100 and  
HBLDS100T Series, cULus, NSF, CE, UL 508 / UL 60947-4-1A

Features

- Constructed from corrosion and impact resistant UV stabilized non-metallic material
- Rounded sloped top enclosure supports best practices in hygienic design by shedding dirt and debris
- IP69k and Type 4X,12K water ingress protection and Certified by NSF for hygiene in food processing applications
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Product rating are permanently laser-marked and will not wash off
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Truly captive screws prevent lost screws

Application

Heavy Duty Industrial and/or Washdown

General

|                              |                                                    |
|------------------------------|----------------------------------------------------|
| Catalog Number               | HBLDS100RC                                         |
| Color                        | Gray                                               |
| Enclosure Type               | IP69k and UL Type 4X, 12                           |
| Environmental Conditions     | Indoor and Outdoor                                 |
| Ingress Protection           | IP69k, NEMA Type 4X, 12                            |
| Material - Mounting Hardware | Stainless Steel Screw Mounting                     |
| Operating Cycles             | 10,000 Cycles Minimum                              |
| Operating Temperature        | Without Impact Maximum continuous 75°C and minimum |

|                |                                                                                                                                                                             |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Series         | -40 °C                                                                                                                                                                      |
| Specifications | Non-Fused <ul style="list-style-type: none"><li>• Enclosure Gasket - Neoprene</li><li>• Handle - Valox®</li><li>• Shaft (Unfused) - Valox®</li><li>• Top - Valox®</li></ul> |
| Style          | Replacement Cover                                                                                                                                                           |
| Type           | Accessories                                                                                                                                                                 |
| UPC            | 783585763408                                                                                                                                                                |

Dimensions

|        |        |
|--------|--------|
| Weight | 1.2 lb |
|--------|--------|

Electrical Ratings

|                           |       |
|---------------------------|-------|
| Current / Amperage Rating | 100 A |
|---------------------------|-------|

Certifications And Compliance

|                      |              |
|----------------------|--------------|
| Industry Standard(s) | cULus Listed |
|----------------------|--------------|

Product Assets

[Brochures - Circuit-Lock® Motor Disconnects](#)  
[Catalog Page - WDK F-8 Catalog Page](#)  
[Installation Manuals - HUBBELL 60A & 100A CIRCUIT-LOCK DISCONNECT SWITCH | Installation manual](#)  
[Literature - Circuit-Lock® Rounded Sloped Top Motor Disconnects](#)  
[Sales Drawings - M-14723](#)  
[Specifications - HBLDS100RC](#)  
[Warranty - Industrial & Commercial Products](#)