

# Industrial Grade, MotorQuick Disconnect, Unfused Switch, 3 Pole, 30A 600V AC,IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure, 5' Pre-Wired Female Cable

By Hubbell Wiring Device-Kellem

Catalog # [HBLDS30MQ5](#)

Industrial Grade, MotorQuick Disconnect, Unfused Switch, 3 Pole, 30A 600V AC,IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure, 5' Pre-Wired Female Cable, cULus, NSF, CE, UL 508 / UL 60947-4-1A



## Application

Heavy Duty Industrial and/or Washdown

## Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current & voltage
- Electrical - Dielectric Voltage - Withstands 3000V AC minimum
- Electrical - Max. Working Voltage - 600V AC RMS
- Environmental - Flammability - UL94-5VA and VO Classification
- Environmental - Operating Temperature - Max Continuous 75°C, Min Continuous -40°C w/o impact
- Environmental - UV Resistance - All materials are UV stabilized
- Mechanical - Impact Resistance - In accordance with UL 746C
- Mechanical - Mounting - Non-Metallic - External fully adjustable feet
- Mechanical - Product Identification - Identification and ratings are part of external label
- Mechanical - Terminal Identification - In accordance with UL, CSA and international conventions

## General

Catalog Number	HBLDS30MQ5
Color	Gray
Enclosure Type	IP69k and UL Type 4X, 12
Environmental Conditions	Indoor and Outdoor
Horsepower - Maximum	15
Ingress Protection	IP69k, NEMA Type 4X, 12
Material - Mounting Hardware	Stainless Steel Screw Mounting
Mounting Method	External fully adjustable feet
Operating Cycles	10,000 Cycles Minimum
Operating Temperature	Without Impact Maximum continuous 75°C and minimum

Series  
Specifications

-40 °C  
Non-Fused  
• Base - Valox®  
• Enclosure Gasket - Neoprene  
• Handle - Valox®  
• Shaft (Unfused) - Valox®  
• Top - Valox®  
Heavy Duty  
Disconnect Switches  
783585763217

Style  
Type  
UPC

## Dimensions

Height 4.12 in  
Hub Size 3/4"  
Weight 4.9 lb

## Electrical Ratings

Current / Amperage Rating 30 A  
Dielectric Strength 2,200V AC minimum for 1 minute

## Conductor Related

Wire Size #14 AWG to #8AWG

## Certifications And Compliance

Industry Standard(s) cULus Listed

## Product Assets

[Brochures - Circuit-Lock® Motor Disconnects](#)  
[Catalog Page - WDK F-13 Catalog Page](#)  
[Installation Manuals - HUBBELL 30 AMP CIRCUIT-LOCK DISCONNECT SWITCH | Installation manual](#)

Literature - Circuit-Lock® Rounded Sloped Top Motor  
Disconnects  
Specifications - HBLDS30MQ5

Warranty - Industrial & Commercial Products  
Video - Circuit-Lock® Rounded Sloped Top Motor Disconnects



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved  
WDK-HBLDS30MQ5-SPEC-EN | REV 3/2025