

# Industrial Grade, Motor Disconnect, Unfused Switch, Non-Metallic Sloped Version Replacement Cover for 30A HBLDS30VFD With inTOUCH Installation Free LED Phase Indication - HBLDS30 and HBLDS30T Series

By Hubbell Wiring Device-Kellems  
Catalog # [HBLDS30RVFDRCP](#)

Industrial Grade, Motor Disconnect, Unfused Switch, Non-Metallic Sloped Replacement Cover for 30A HBLDS30 and HBLDS30T Series With inTOUCH Installation Free LED Phase Indication and HBLAC2, cULus, NSF, CE, UL 508 / UL 60947-4-1A

## Features

- Constructed from corrosion and impact resistant UV stabilized non-metallic material
- IP69k and Type 4X,12K water ingress protection
- IP69k and Type 4X,12K water ingress protection and Certified by NSF for hygiene in food processing applications
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Product rating are permanently laser-marked and will not wash off
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Six highly visible integral phase identification LEDs for use on 3 Phase Y or Delta systems provide secondary means of visual confirmation of make/break on all phases

## Application

Heavy Duty Industrial and/or Washdown

## General

Catalog Number	HBLDS30RVFDRCP
Color	Gray
Enclosure Type	IP69k and UL Type 4X, 12
Environmental Conditions	Indoor and Outdoor
Ingress Protection	IP69k, NEMA Type 4X, 12
Material - Mounting Hardware	Stainless Steel Screw Mounting



Operating Cycles	10,000 Cycles Minimum
Operating Temperature	Without Impact Maximum continuous 75°C and minimum -40 °C
Series	Non-Fused
Specifications	<ul style="list-style-type: none"><li>• Enclosure Gasket - Neoprene</li><li>• Handle - Valox®</li><li>• Shaft (Unfused) - Valox®</li><li>• Top - Valox®</li></ul>
Style	Replacement Cover
Type	Accessories
UPC	783585763149
Dimensions	
Weight	0.9 lb
<b>Certifications And Compliance</b>	
Industry Standard(s)	cULus Listed
<b>Product Assets</b>	
<a href="#">Brochures - Circuit-Lock® Motor Disconnects</a>	
<a href="#">Installation Manuals - HUBBELL 30 AMP CIRCUIT-LOCK DISCONNECT SWITCH   Installation manual</a>	
<a href="#">Literature - Circuit-Lock® Rounded Sloped Top Motor Disconnects</a>	
<a href="#">Specifications - HBLDS30RVFDRCP</a>	
<a href="#">Warranty - Industrial &amp; Commercial Products</a>	
<a href="#">Video - Circuit-Lock® Rounded Sloped Top Motor Disconnects</a>	



A Hubbell brand