

# Industrial Grade, Motor Disconnect, Unfused, 3 Pole, 30A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12 Non-Metallic Sloped Top Enclosure, HBLAC2 Aux Contact

By Hubbell Wiring Device-Kellems  
Catalog # [HBLDS30VFD](#)

Industrial Grade, Motor Disconnect, Unfused, 3 Pole, 30A 600V AC, Screw Terminals, IP69k, NEMA Type 4X, 12, Non-Metallic Sloped Top Enclosure, HBLAC2 Aux Contact, cULus, NSF, CE, UL 508 / UL 60947-4-1A

## Features

- Constructed from corrosion and impact resistant UV stabilized non-metallic material
- Rounded sloped top enclosure supports best practices in hygienic design by shedding dirt and debris
- IP69k and Type 4X,12K water ingress protection and Certified by NSF for hygiene in food processing applications
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Product rating are permanently laser-marked and will not wash off
- Highly visible red handle can be locked in the OFF position as a method of compliance with OSHA Lockout/Tagout requirements
- Factory installed HBLAC2 auxiliary contact is "Break Before Main Break", 1 set of N/O contacts for VFD applications

## Application

Heavy Duty Industrial and/or Washdown

## Performance

- Electrical - Current Interrupting - Certified for current interrupting at full rated current & voltage
- Electrical - Dielectric Voltage - Withstands 3000V AC minimum
- Electrical - Max. Working Voltage - 600V AC RMS
- Environmental - Flammability - UL94-5VA and V0 Classification
- Environmental - Operating Temperature - Max Continuous 75°C, Min Continuous -40°C w/o impact
- Environmental - UV Resistance - All materials are UV stabilized
- Mechanical - Impact Resistance - In accordance with UL 746C
- Mechanical - Mounting - Non-Metallic - External fully adjustable feet



- Mechanical - Product Identification - Identification and ratings are part of external label
- Mechanical - Terminal Identification - In accordance with UL, CSA and international conventions

## General

Catalog Number	HBLDS30VFD
Color	Gray
Enclosure Type	IP69k and UL Type 4X, 12
Environmental Conditions	Indoor and Outdoor
Horsepower - Maximum	15
Ingress Protection	IP69k, NEMA Type 4X, 12
Material - Mounting Hardware	Stainless Steel Screw Mounting
Mounting Method	External fully adjustable feet
Operating Cycles	10,000 Cycles Minimum
Operating Temperature	Without Impact Maximum continuous 75°C and minimum -40 °C

Series	Non-Fused
Specifications	<ul style="list-style-type: none"><li>• Base - Valox®</li><li>• Enclosure Gasket - Neoprene</li><li>• Handle - Valox®</li><li>• Shaft (Unfused) - Valox®</li><li>• Top - Valox®</li></ul>
Style	Heavy Duty
Type	Disconnect Switches
UPC	783585763064

## Dimensions

Height	4.12 in
Hub Size	3/4"
Weight	2.8 lb

## Electrical Ratings

Current / Amperage Rating	30 A
---------------------------	------

Dielectric Strength Withstands 3000V AC minimum

### Conductor Related

Wire Size #14 AWG to #8AWG

### Certifications And Compliance

Industry Standard(s) cULus Listed

### Product Assets

[Brochures - Circuit-Lock® Motor Disconnects](#)

[Catalog Page - WDK F-5 Catalog Page](#)

[Installation Manuals - HUBBELL 30 AMP CIRCUIT-LOCK DISCONNECT SWITCH | Installation manual](#)

[Literature - Circuit-Lock® Rounded Sloped Top Motor Disconnects](#)

[Specifications - HBLDS30VFD](#)

[Warranty - Industrial & Commercial Products](#)

[Video - Circuit-Lock® Rounded Sloped Top Motor Disconnects](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved  
WDK-HBLDS30VFD-SPEC-EN | REV 10/2024