

Detailed information for: S2C-H10

This page contains technical data sheet, documents library and links to offering related to this product. If you require any other information, please contact us using form located at the bottom of the page.

S2C-H10

General Information

Extended Product Type:	S2C-H10
Product ID:	2CDS200970R0002
EAN:	4016779645522
Catalog Description:	S2C-H10 - Auxiliary Contact
Long Description:	Indication of the position of the device's contacts. S2C-H01 is the opening device and S2C-H10 the closing device. Compared to the S2C-S/H6R, the S2C-H10 entails less cost and many practical benefits. It can be fitted at the bottom of the MCBs and RCDs and is thus much more convenient for retrofitting than the side-mounted device because not all MCBs have to be removed from the rail first. And even when the MCBs affected are connected to a busbar, they do not have to be removed. 50% space can be saved. Suitable for MCBs S200 series, electronic RCBOs DSE200 series.

Categories

Products » Low Voltage Products and Systems » Modular DIN Rail Products » Miniature Circuit Breakers MCBs Accessories » Auxiliary / Signal Contacts

Ordering

EAN:	4016779645522
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	110 mm
Product Net Height:	21 mm
Product Net Depth / Length:	125 mm
Product Net Weight:	0.019 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	20 mm
Package Level 1 Height:	125 mm
Package Level 1 Depth / Length:	106 mm
Package Level 1 Gross Weight:	0.019 kg
Package Level 1 EAN:	4016779645522
Package Level 2 Units:	60 piece
Package Level 2 Width:	140 mm
Package Level 2 Height:	275 mm

Package Level 2 Depth / Length: 433 mm

Package Level 2 Gross Weight: 2.6 kg

Package Level 2 EAN: 4016779830393

Environmental

RoHS Status: Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Accessory Type: Auxiliary Contact

Function: Auxiliary Contact

Power Loss: 0,5 W

Product Main Type: S2C

Product Name: Auxiliary Contact

RoHS Date: 0335

Standards: GB14048.5
CSA 22.2 No. 235
UL 1077

Suitable For: S200
S200M
S200P
S200S
DSE200

Suitable for Product Class: Miniature Circuit Breaker
Residual Current Device

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: [9AKK106930A8017](#)

Declaration of Conformity - CE: [2CDK400628D2701](#)

Environmental Information: [2CDK400571D0201](#)

Instructions and Manuals: [GHS2007009P0008](#)

RoHS Information: [2CDK440032D0203](#)

Classifications

eClass: 7.0 27143502

E-nummer: 2102505

ETIM 4: EC001286 - Auxiliary contact unit for distribution board

ETIM 5: EC001286 - Auxiliary contact unit for distribution board

ETIM 6: EC001286 - Auxiliary contact unit for distribution board

UNSPSC: 39121614



© Copyright 2018 ABB