



SNA Terminal Blocks

T&B Catalog Number:

1SNA400370R2400

UPC Number:

80432556399

Status:

Active

Description:

Gray, feed through terminal block with 26 mm spacing, 230 Amp rated UL current with screw clamp connection that accepts 2-0000 AWG UL wire range

Features

Self-locking clamp design prevents screw loosening

Funneled side entry for up to two ferruled or non-ferruled solid or stranded wires

Touch-safe IP20 protection

High quality steel offers a very high over-torque resistance

Compensates for the flattening of copper under contact pressure

Clamp is protected from harsh environments by a zinc bichromate surface treatment

Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

General

Style	Feed Through
Color	Gray
Mounting	DIN 1-3
Series	D 95/26
Connection Technology	Screw Clamp
UL Wire Range (AWG)	2-0000
Rated IEC Wire Range (Solid) (mm ²)	95

Dimension Information

L x W x H (mm)	87 x 26 x 79.5
Spacing (mm)	26
L x W x H (in)	3.43 x 1.02 x 3.13
Spacing (inches)	1.024

Specifications

UL Current (Amps)	230
UL Voltage (VAC)	600
IEC Voltage (VAC)	1000
IEC Current (Amps)	232
CSA Voltage (VAC)	600
CSA Current (Amps)	230

Packaging

T&B Order Multiple	10
T&B Inner Pack	10
Package in Units	30
T&B Sold in UOM	Each
T&B Weight Per UOM	0.48 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com