



Specific Terminal Blocks

T&B Catalog Number:

011519103

UPC Number:

66201995614

Status:

Active

Description:

Gray, quick connect terminal block with 6 mm spacing, 25 Amp rated UL current that accepts 10 AWG UL wire

Features

Includes IP20 protection

Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

General

Style	Feed Through
Color	Gray
Mounting	DIN 1-3
Series	M2,5/6.2G.2G
Connection Technology	Quick-Connect
Rated IEC Wire Range (Solid) (mm ²)	2.5
Rated CSA Wire Size (AWG)	12

Dimension Information

L x W x H (mm)	44.5 x 53
Spacing (mm)	6
L x W x H (in)	1.75 x 2.09
Spacing (inches)	0.238

Specifications

UL Current (Amps)	25
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	10
IEC Voltage (VAC)	630
IEC Current (Amps)	20

Packaging

T&B Order Multiple	50
T&B Inner Pack	50
Package in Units	1000
T&B Sold in UOM	Each
T&B Weight Per UOM	0.02 lbs. Each

Certifications

Approvals	IEC, UL, CSA
-----------	--------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com