



SNA Terminal Blocks

T&B Catalog Number:

UPC Number:

011566222

Status:

66201995749

Description:

Active

Gray, fuse holder block with 8 mm spacing, 10 Amp rated UL current with screw clamp connection that accepts 22-12 AWG UL wire range

Features

	Includes 2mm test socket
	Self-locking clamp design prevents screw loosening
	Quick fuse installation and replacement
	Touch-safe IP20 protection
	High quality steel offers a very high over-torque resistance
	Compensates for the flattening of copper under contact pressure
	Clamp is protected from harsh environments by a zinc bichromate surface treatment

Application

	For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.
--	---

General

Style	Fuse Holder
Color	Gray
Mounting	DIN 1-3
Series	M 4/8.SF
Connection Technology	Screw Clamp
UL Wire Range (AWG)	22-12
Rated IEC Wire Range (Solid) (mm ²)	4
Rated CSA Wire Size (AWG)	12

Dimension Information

L x W x H (mm)	56.5 x 8 x 53.5
Spacing (mm)	8
L x W x H (in)	2.23 x .197 x 2.10
Spacing (inches)	0.315

Specifications

UL Current (Amps)	10
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	12
IEC Voltage (VAC)	630
IEC Current (Amps)	6.3
CSA Voltage (VAC)	250
CSA Current (Amps)	10

Packaging

T&B Order Multiple	50
T&B Inner Pack	50
Package in Units	450
T&B Sold in UOM	Each

T&B Weight Per UOM	0.03 lbs. Each
--------------------	----------------

Certifications

Approvals	UL, IEC, CSA
-----------	--------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com