



## SNA Terminal Blocks

### T&B Catalog Number:

010504906

UPC Number:

66201995359

Status:

Active

Description:

Orange, feed through terminal block with 6 mm spacing, 20 Amp rated UL current with screw clamp connection that accepts 22-12 AWG UL wire range

### Features

|  |                                                                                    |
|--|------------------------------------------------------------------------------------|
|  | Double deck                                                                        |
|  | Self-locking clamp design prevents screw loosening                                 |
|  | Funneled side entry for up to two ferruled or non-ferruled solid or stranded wires |
|  | Touch-safe IP20 protection                                                         |
|  | High quality steel offers a very high over-torque resistance                       |
|  | Compensates for the flattening of copper under contact pressure                    |
|  | Clamp is protected from harsh environments by a zinc bichromate surface treatment  |

### Application

|  |                                                                                                                                                                                                                   |
|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc. |
|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### General

|                                                 |                          |
|-------------------------------------------------|--------------------------|
| Style                                           | Double Deck Feed Through |
| Color                                           | Orange                   |
| Mounting                                        | DIN 1-3                  |
| Series                                          | M 4/6.D2                 |
| Connection Technology                           | Screw Clamp              |
| UL Wire Range (AWG)                             | 22-12                    |
| Rated IEC Wire Range (Solid) (mm <sup>2</sup> ) | 4                        |
| Rated CSA Wire Size (AWG)                       | 12                       |

### Dimension Information

|                  |                     |
|------------------|---------------------|
| L x W x H (mm)   | 65.5 x 6 x 64.5     |
| Spacing (mm)     | 6                   |
| L x W x H (in)   | 2.57 x 0.238 x 2.34 |
| Spacing (inches) | 0.236               |

### Specifications

|                          |     |
|--------------------------|-----|
| UL Current (Amps)        | 20  |
| UL Voltage (VAC)         | 600 |
| Rated UL Wire Size (AWG) | 12  |
| IEC Voltage (VAC)        | 800 |
| IEC Current (Amps)       | 32  |
| CSA Voltage (VAC)        | 300 |
| CSA Current (Amps)       | 25  |

### Packaging

|                    |    |
|--------------------|----|
| T&B Order Multiple | 50 |
| T&B Inner Pack     | 50 |

|                    |                |
|--------------------|----------------|
| Package in Units   | 1000           |
| T&B Sold in UOM    | Each           |
| T&B Weight Per UOM | 0.04 lbs. Each |

#### **Certifications**

|           |              |
|-----------|--------------|
| Approvals | UL, IEC, CSA |
|-----------|--------------|

#### **For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)