

SNA Terminal Blocks T&B Catalog Number:

012512401

UPC Number: 66201995894 Status: Active

Description:

Blue, feed through terminal block with 16 mm spacing, 150 Amp rated UL current with screw clamp connection that accepts 10-0 AWG UL wire range

range	
Features	
	Self-locking clamp design prevents screw loosening
	Funneled side entry for up to two ferruled or non-
	ferruled solid or stranded wires
	Touch-safe IP20 protection
	High quality steel offers a very high over-torque re-
	sistance
	Compensates for the flattening of copper under
	contact pressure
	Clamp is protected from harsh environments by a
	zinc bichromate surface treatment
Application	
	For use with applications ranging from standard
	distribution and control panels, to specialized ap-
	plications in key industries such as traction, ener-
	gy, maritime, explosive atmospheres, material han-
	dling, etc.
General	G.
Style	Feed Through
Color	Blue
Mounting	DIN 1-3
Series	M 35/16
Connection Technology	Screw Clamp
UL Wire Range (AWG)	10-0
Rated IEC Wire Range (Solid) (mm2)	35
Dimension Information	
L v M v H (mm)	49 x 16 x 59
L x W x H (mm) Spacing (mm)	49 X 16 X 59
L x W x H (in)	1.93 x 0.630 x 2.32
Spacing (inches)	0.63
Specifications	0.00
opeomeaneme	
UL Current (Amps)	150
UL Voltage (VAC)	600
IEC Voltage (VAC)	800
IEC Current (Amps)	125
CSA Voltage (VAC)	600
CSA Current (Amps)	140
Packaging	
T&B Order Multiple	20
T&B Inner Pack	20
Package in Units	300
T&B Sold in UOM	Each
T&B Weight Per UOM	0.11 lbs. Each



Certifications

Approvals UL, IEC, CSA

For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com