Thomas@Betts



SNA Terminal Blocks T&B Catalog Number:

029020111

UPC Number: 66201997030 **Status:** Active

Description:

Gray miniblock terminal block with 5mm spacing and 15 amp UL rated current with spring clamp connection

current with spring clamp connect	tion
Features	
	Touch-safe IP20 protection
Application	Todal care ii 20 protodion
- грриошен	
	For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.
General	
Style	Miniblock
Color	Gray
Mounting	DIN 2
Series	DR 2.5/5.2L
Connection Technology	Spring Clamp
UL Wire Range (AWG)	26-12
Rated IEC Wire Range (Solid) (mm2)	2.5
Rated CSA Wire Size (AWG)	12
Dimension Information	
Spacing (mm)	5
Spacing (mm) Spacing (inches)	0.198
Specifications	0.190
opecinications -	
UL Current (Amps)	15
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	12
IEC Voltage (VAC)	800
IEC Current (Amps)	24
Packaging	
T&B Order Multiple	100
T&B Inner Pack	100
Package in Units	1000

5 lbs. per 1000

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125

T&B Weight Per UOM

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com