

SNA Terminal Blocks T&B Catalog Number:

039907102

UPC Number: 66201997818

Status: Active

Description:

Gray, angled terminal block with 5 mm spacing, 15 amp rated UL current with spring clamp connection that accepts 26-12 AWG UL wire size

Features

	Touch-safe IP20 protection
Application	·
	For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.
General	
Style	Feed Through
Color	Gray
Mounting	DIN 3
Series	D 2.5/5.I.3L
Connection Technology	Spring Clamp
UL Wire Range (AWG)	26-12
Dimension Information	
Spacing (mm)	5
Spacing (inches)	0.198
Specifications	
UL Current (Amps)	15
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	12
IEC Voltage (VAC)	800
IEC Current (Amps)	24
Packaging	
T&B Order Multiple	50
T&B Inner Pack	50
Package in Units	900
T&B Sold in UOM	Each
T&B Weight Per UOM	0.01 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com