



SNA Terminal Blocks T&B Catalog Number:

UPC Number:

019916800

Status:

66201996518

Description:

Active

Black, fuse holder block with 13 mm spacing, 25 Amp rated UL current with screw clamp connection that accepts 22 - 10 AWG UL wire range

Features

	Includes neon, 110-230 V fusion indicator
	Self-locking clamp design prevents screw loosening
	Quick fuse installation and replacement
	Touch-safe IP20 protection
	High quality steel offers a very high over-torque resistance
	Compensates for the flattening of copper under contact pressure
	Clamp is protected from harsh environments by a zinc bichromate surface treatment

Application

	For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.
--	---

General

Style	Fuse Holder
Color	Black
Mounting	DIN 1-3
Series	ML 10/13.SF
Connection Technology	Screw Clamp
UL Wire Range (AWG)	22-10
Rated IEC Wire Range (Solid) (mm ²)	10
Rated CSA Wire Size (AWG)	8

Dimension Information

L x W x H (mm)	85 x 32 x 70.5
Spacing (mm)	13
L x W x H (in)	3.35 x 1.25 x 2.77
Spacing (inches)	0.512

Specifications

UL Current (Amps)	25
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	10
IEC Voltage (VAC)	800
IEC Current (Amps)	16
CSA Voltage (VAC)	600
CSA Current (Amps)	25

Packaging

T&B Order Multiple	20
T&B Inner Pack	20
Package in Units	200
T&B Sold in UOM	Each

T&B Weight Per UOM	0.12 lbs. Each
--------------------	----------------

Certifications

Approvals	UL, IEC, CSA
-----------	--------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com