



SNA Terminal Blocks

T&B Catalog Number:

UPC Number:

Status:

Description:

011526524

66201995641

Active

Gray, standard terminal block with 6 mm spacing, 30 Amp rated UL current that accepts 10 AWG UL wire

Features

Includes IP20 protection

Application

For use with applications ranging from standard distribution and control panels, to specialized applications in key industries such as traction, energy, maritime, explosive atmospheres, material handling, etc.

General

Style	Feed Through
Color	Gray
Mounting	DIN 1-3
Series	MS4/6
Connection Technology	Screw Clamp
Rated IEC Wire Range (Solid) (mm ²)	4
Rated CSA Wire Size (AWG)	12

Dimension Information

L x W x H (mm)	41 x 43.5
Spacing (mm)	6
L x W x H (in)	1.61 x 1.71
Spacing (inches)	0.238

Specifications

UL Current (Amps)	30
UL Voltage (VAC)	600
Rated UL Wire Size (AWG)	10
IEC Voltage (VAC)	630
IEC Current (Amps)	32

Packaging

T&B Order Multiple	100
T&B Inner Pack	100
Package in Units	1500
T&B Sold in UOM	Each
T&B Weight Per UOM	1.5 lbs. per 100

Certifications

Approvals	IEC, UL, CSA
-----------	--------------

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com